



# Printer Specification Information

## KR203 Kiosk Printer

**PRINTER NAME:** KR200 Series  
**PRINTER MODEL:** KR203



---

### STANDARD FEATURES

- Direct thermal receipt printing for 58 to 82.5 width media
- Patented looping presenter with pull detector
- Integrated cutter
- Auto media loading
- Horizontal and vertical mounting capability
- Various media mounting options behind and below give flexibility to kiosk design, up to 9.8"/250 mm diameter media rolls
- USB connectivity
- 203-dpi print resolution
- Windows® drivers for plug and play
- Prints any font, bar code, and graphics supported by the application
- Automatic and continuous status monitoring for media condition and errors

---

### PRINTER SPECIFICATIONS

Resolution: 203 dpi/ 8 dots per mm  
Max print width: 3.1"/ 80 mm  
Print length: 3.6"/92 mm (Min) 23.6"/ 600 mm (Max)  
Print speed: 6.0"/152 mm per second  
Media sensors: Out-of-paper, paper in Presenter, black mark, and input for external paper-low sensor

---

### MEDIA CHARACTERISTICS

Media width: 2.3"/58 mm, 2.4"/60 mm, 3.15"/80 mm, and 3.3"/82.5 mm supported  
Max media roll size: 9.8"/ 250 mm  
Core diameter: 1"/25 mm standard, 1/2"/12 mm with optional accessory  
Media thickness: 0.002"/ 0.054 mm to 0.004"/ 0.11 mm  
Media types: Roll or fanfold paper

---

### OPERATING CHARACTERISTICS

Operating Tem 32° F/0° C to 122° F/50° C  
Storage Temp: -22° F/-30° C to 149° F/65° C  
Operating Humidity: 20% to 80% non-condensing  
Storage Humidity: 10% to 95 non-condensing excluding paper  
Electrical: 24Vdc +/-5% average of 2A when printing

# Printer Specification Information

## KR203 Kiosk Printer

---

### PHYSICAL CHARACTERISTICS

Width: 4.2"/107 mm

Height: 2.7"/69 mm

Depth: 5.7"/145 mm

Weight: 2.4lbs/1.1 kg

---

### COMMUNICATIONS AND INTERFACE CAPABILITIES

Connectivity: USB

Operating Systems: Windows 7, Vista, XP, Server 2003, Server 2008 (32 and 64 bit O/S support for all drivers)

---

### OPTIONS AND ACCESSORIES

- Media guides 58, 60, 80, 82.5 mm
- Roll Holder "universal" variable position, 7.9"/200 mm dia max
- Adapter for roll holder below position, 9.8"/250 mm dia max
- Roll Holder Wall Mount, 5.9"/150 mm dia max
- Quick Fit Hubs for easy mounting and removal of printer
- Paper-Low Sensor with 11.8"/300 mm cable
- Paper-Low Sensor with 19.7"/500 mm cable
- Large media roll accessory to remove print artifacts from media rolls over 6"/150 mm in diameter
- Adapter plate and spindle for 0.5"/12 mm media rolls
- Output bezel for easier integration
- Output shutter to protect the printer from intrusion or damage
- Accessory kits for quick deployment

### Zebra Technologies International, LLC

333 Corporate Woods Parkway » Vernon Hills, IL 60061-3109 USA T+1 847 793 2600 F+1 847 913 8766 [www.zebra.com](http://www.zebra.com)

